



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 1 sur 18

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

- Product name: **KENNOL CVT FLUID**

1.2. Relevant identified uses of the substance or mixture and uses advised against

- Commercial use: Automatic transmission oil (for more details, please report back to the technical manual)

1.3. Details of the supplier of the Safety Data Sheet

- Fournisseur **ACCOR LUBRIFIANTS SA**

Adresse : 8 Rue du Mans - BP 30406 - 49304 CHOLET CEDEX

Téléphone : 02.41.75.26.70

Télécopie : 02.41.62.67.02

Contact e-mail : emilie.auribault@accor-lubrifiants.com

1.4. Emergency telephone number

In France, the valid emergency number is the ORFILA (INRS) number: + 33 (0)1 45 42 59 59. This telephone number gives contacts of all French poison centers ("centres anti-poison et de toxicovigilance"). These information centers provide you with free medical advice (except the cost of call), 24 hours a day, 7 days a week. For the information related to other countries, see the web page dedicated to national helpdesks of the ECHA website (European Chemicals Agency) that lists all the information by country:

<http://echa.europa.eu/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks>

SECTION 2 - HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification CE 1272/2008 (CLP)

H317 – Cutaneous sensitization– category 1

H412 –Harmful to aquatic life with long lasting effects - Chronic hazard category 3 (CLP Aquatic Chronic 3)



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 2 sur 18

2.2. Label elements

Label Conforms to Norm (CE) N° 1272/2008 (CLP):

Hazard pictogram(s):



Signal word(s): WARNING

Hazard statement(s):

H317 May cause an allergic skin reaction.

H412 –Harmful to aquatic life with long lasting effects

Additional phrases:

CONTAINS: Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs (N°CE : 471-920-1).

Additional phrases 2:

EUH 208 - Contains C14-18 alpha-olefin epoxide, reaction products with boric acid. May cause an allergic reaction.

EUH 208- Contains 1,2-Propanediol, 3-amino-, N,N-dicoco alkyl derivs. May cause an allergic reaction.

Precautionary statement(s) – Prevention

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing vapours

P273 – Avoid release to the environment

Precautionary statement(s) - Intervention

P302 + P352 – IF ON SKIN: wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: get medical advice/attention.

P363 – Wash contaminated clothing before reuse.

Precautionary advice- Storage

None

Precautionary advice - Elimination

P501 - Dispose of contents/container to a hazardous waste collection center, as per national regulation



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 3 sur 18

2.3. Other hazards

Flammable and combustible product if heated.

The oil mist may irritate eyes and breathing apparatus.

Prolonged and frequent contact may dry and irritate the skin and cause a rash.

The used oil can contain dangerous impurities.

Possibility of soil and groundwater contamination.



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 4 sur 18

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

- Chemical nature: Product formulated from base oils and additives

- Dangerous components:

COMPONENTS	Percentage (in weight)	CLP Classification (EC) No 1272/2008	NUMBERS
			INDEX CE CAS Registration
Petroleum base oil	< 100 %	Asp. Tox. 1, H304	Mixture (*)
Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs	< 3%	Skin Sens. 1B; H317	- 471-920-1 - 01-0000019770-68
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	< 3%	Aquatic Chronic 4; H413	- Confidential - 01-2119488911-28
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich	< 3%	Aquatic Chronic 2; H411	- 800-172-4 - 01-2119969520-35
Alkyl borate	< 3%	Eye Dam. 2; H319 Aquatic Chronic 3; H413	confidentiel
Dibutyl phosphite	< 3%	Eye Dam. 2; H319 Skin Corr. 2; H315	- 217-316-1 - -
C14-18 alpha-olefin epoxide, reaction products with boric acid	< 0.5%	Skin Sens. 1B; H317	- Polymere - 01-2119976364-28
1,2-Propanediol, 3-amino-, N,N-dicoco alkyl derivs.	< 0.5%	Aquatic Chronic 3; H412 Skin Sens. 1B; H317	- 482-000-4 - 01-0000020142-86
Diphenylamine	< 0.5%	Acute Tox. 3; H331 Acute Tox. 3; H311 Acute Tox. 3; H301 STOT RE 2; H373 Aquatic Acute 1; H400	- 204-539-4 - -



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 5 sur 18

		Aquatic Chronic 1; H410 Eye Dam. 2; H319	
Ethanol, 2,2'-iminobis-, N-tallow alkyl derivatives	< 0.5%	Eye Dam. 1; H318 Skin Corr. 1C; H314 Aquatic Chronic 1; H410 (facteur M 1) Aquatic Acute 1; H400 (factor M 10) Acute Tox. 4; H302 Met. Corr. 1; H290	- 263-177-5 - -

(*) Mixture: The mineral oil contained may be described by one or more mentions amongst the following: N° CE 265-157-1, Registration n° 01-2119484627-25, distillates (petroleum) hydrotreated heavy paraffinic; N° CE 265-169-7, Registration n° 01-2119471299-27, heavy distillates (petroleum), solvent-dewaxed; N° CE265-158-7, Registration n° 01-2119487077-29, distillates (petroleum) hydrotreated light paraffinic ; N° CE 265-159-2, Registration n° 01-2119480132-48, light distillates (petroleum), solvent-dewaxed, light paraffinic fraction.

The whole of the text of risk phrases and hazard statements of this section 3 appears in Section 16.

SECTION 4 - FIRST AID MEASURES

4.1. Description of first aid measures

If feeling unwell seriously or persistently, immediately seek medical attention

Inhalation:

Move the subject away from the polluted area.

Take affected person into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

In the event of faintness, consult a doctor.

Skin contact:

Wash the skin with soap and water.

In case of persistent irritation of the skin, consult a doctor.

Wash contaminated clothing before reuse.

Eye contact:



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 6 sur 18

Rinse out with plenty of water for at least 30 minutes with the eyelid held wide open. Consult an ophthalmologist if the irritation persists.

Ingestion:

DO NOT INDUCE VOMITING: seek medical or poison center advice immediately.

Move the person who is vomiting from his back onto his side.

Self-protection of the first aider:

When providing first aid, protect yourself against the exposure to chemicals or blood-borne diseases wearing gloves, masks as well as eye protection equipment. After performing first aid, wash the exposed skin with soap and water.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physician: treat symptomatically.

SECTION 5 - MESURES DE LUTTE CONTRE L'INCENDIE

5.1. Moyens d'extinction

Moyens d'extinction appropriés : CO₂, poudre sèche, émulseur polyvalent ; l'eau peut être utilisée pour refroidir et protéger les récipients de produit exposés.

Produits extincteurs déconseillés pour des raisons de sécurité: Jet d'eau à grand débit

5.2. Dangers particuliers résultant de la substance ou du mélange

Pour plus d'informations, voir section 10.

5.3. Conseils aux pompiers

Il est recommandé de porter un appareil respiratoire autonome. L'eau peut éclabousser les éléments proches. Utiliser de l'eau pour refroidir les récipients exposés.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 7 sur 18

Personal protective equipment must be worn. Avoid all contact with skin. If the spill occurs in a closed environment or other area with poor ventilation, ventilate before entering the area.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case product reaches water or sewage system.
Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Soak up to recycle and/or dispose of. The remaining liquid can be absorbed with inert material.

6.4. Reference to other sections

To obtain information about safe handling, please see chapter 7.
To obtain information about personal protective equipment, please see chapter 8.
To obtain information about elimination, please see chapter 13.

SECTION 7 - HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product.
Keep containers closed when unused. Do not discharge into drains or the environment, dispose of this product to an officially approved waste collection center. Use appropriate containment to avoid environmental contamination. Avoid skin contact. Wash thoroughly after handling. Wash contaminated clothing before reuse. Empty containers retain product residue that may present product hazards. Dispose of packaging and containers according to local, regional, national and international regulations.

Pumping temperature

Ambient

Maximal handling temperature

70 °C, 158 °F

Maximal loading temperature

Not identified

7.2. Conditions for safe storage, including any incompatibilities

Take precautions to avoid all release in the environment. To know incompatible materials, see section 10.
Maximal preservation temperature
45 °C, 113 °F

7.3. Specific end use(s)



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 8 sur 18

No other important information available.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limit values:

Where conditions are created for the formation of mists, check the PEL of 5 mg by cubic meter of OSHA and TWA of 5mg by cubic meter of ACGIH to control possible oil mists.

Recommended control procedures: this product contains ingredients presenting exposure limits, the working atmosphere or living organisms can be necessary to determine the efficiency of ventilation or other control measures and/or the necessity to use breathing apparatus. It is worth to mention to the European EN 689 norm referring to methods to evaluate the exposure by inhalation to chemical agents and to documents of general national policy referring to methods to determine hazardous substances.

8.2. Exposure controls

The appropriate control measures for a particular workplace depend on the way the product is used and on potential exposure.

Personal protective equipment:

The product must be handled in closed containers and equipment, in which case mechanical local ventilation should be sufficient. Local exhaust ventilation should be used in places where dusts, mists, steam or gas may leak in the local atmosphere.

Eye/face protection

Goggles.

Skin protection

Nitrile.

Long sleeve shirts are recommended. Use a chemical protection apron if contact with this product can happen. When working with the product heated, use an insulated apron or an insulated chemical protection garment. Wash the contaminated clothing before reuse.

Breathing protection

Use a respirator combined with an organic vapor cartridge as well as a very efficient filter if the exposure limit recommended is exceeded.

Use an insulated breathing apparatus to penetrate in confined space and other spaces poorly ventilated and for decontamination zones where big quantities have been spread.

Hygiene measures

Wash yourself thoroughly after handling this product.



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 9 sur 18

Environmental exposure controls

For more details, see section 6

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1. Appearance

Aspect: Liquid

Density at 20°C (g/cm³): 0,851

Colour: 33,7

Viscosity at 40°C (mm²/s) : > 180

Smell: oil feature

Flash point (closed beaker) (°C): > 170°C

Flow point (°C): < -35

Ignition temperature: Not identified.

Steam pressure at 20°C: Not identified.

Partition coefficient (n-octanol/water): Not identified.

Explosive properties: This product is not known to be explosive.

Oxidizing properties: This product is a non-oxidizing substance.

9.2. Other information

No other important information available.

SECTION 10 - STABILITY AND REACTIVITY

10.1. Reactivity

Carefully consider all information provided in sections 10.2 to 10.6.

10.2. Chemical stability

This product is normally stable with low temperatures and is not decomposed by water.

10.3. Possibility of hazardous reactions

Dangerous reactions: none when used normally.

Dangerous properties: none when used normally.

10.4. Conditions to avoid

High temperature. Excessive heat.

10.5. Incompatible materials



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 10 sur 18

Strong acids. Oxidizing agents.

10.6. Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products with incomplete combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information referred to ingredients.

Petroleum base oil:

Acute toxicity

Very low toxicity:

DL50/oral/rat = > 5000 mg/kg (OECD 401).

DL50/cutaneous/rabbit = > 2000 mg/kg (OECD 402).

CL50/inhalation/4h/rat = > 5.53 mg/L (OECD 403).

Corrosion / skin irritation

Not classified (OECD 404, 405). The mineral oils mist may irritate eyes and breathing apparatus.

The prolonged or repeated skin contact may irritate and cause dermatitis.

Sensitization

Non-sensitizing to the skin (OECD 406).

Subacute and Subchronic Toxicity on a long period

Not classifiable as a human carcinogen. (OECD 451, 453).

Not toxic for reproduction (OECD 421).

Damage to fetus not classifiable (OECD 414).

Genotoxicity tests (in vitro and in vivo) have been negative. (OECD 471, 473, 474, 476)

Specific toxicity for some target organs – unique exposure

No known effects.

Specific toxicity for some target organs – repeated exposure

No known effects

Hazard by aspiration

Aspiration into the lungs can cause chemical pneumonitis that can be fatal.

Other information on acute toxicity

The toxicological data have been reported from products with similar composition.

The used mineral oils may contain an accumulation of harmful contaminants to health and environment.

SECTION 12 - ECOLOGICAL INFORMATION



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 11 sur 18

12.1. Toxicity

The mixture has not been tested, application of the conventional methods from components.

As for the mixture:

Acute toxicity (short term) – Fish: not data available

Acute toxicity (short term) – Shellfish: not data available

Acute toxicity (short term) – Seaweed/aquatic plants: not data available

Acute toxicity (short term) – Other organisms: not data available

Chronic toxicity (long term) – Fish: not data available

Chronic toxicity (long term) – Shellfish: not data available

Chronic toxicity (long term) – Seaweed/aquatic plants: not data available

Chronic toxicity (long term) – Other organisms: not data available

Referring to substances that compose the mixture:

Petroleum base oil:

Very low toxicity:

Acute toxicity for the aquatic environment:

fish: LL50/96h > 100 mg/L; NOEL/96h >= 100 mg/L (OECD 203)

shellfish: EL50/24-48h; NOEL/48-96h; LL50/24-96h > 10 000 mg/L (OECD 202)

seaweed: NOEL/72h >= 100 mg/L (OECD 201)

Chronic toxicity for the aquatic environment:

shellfish: NOEL/21d = 10 mg/L (OECD 211)

fish

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

LC 50 (Zebra fish, 4 DY): > 100 mg/l

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich

LC 50 (Rainbow Trout, 4 DY): 2,4 mg/l

LC 50 (Cyprinodon variegatus, 4 DY): 3,3 mg/l

NOEC (Rainbow Trout, 4 DY): 1 mg/l

Alkyl borate

LC 50 (Zebra fish, 4 DY): 21,17 mg/l

Dibutyl phosphite

LC 50 (Zebra fish, 96 h): 63,4 mg/l

C14-18 alpha-olefin epoxide, reaction products with boric acid

LC 50 (Rainbow Trout, 4 DY): > 100 mg/l

Diphenylamine

LC 50 (Not reported, 2 DY): 2,2 mg/l

Ethanol, 2,2'-iminobis-, N-tallow alkyl derivatives

LC 50 (Not reported, 4 DY): < 1 mg/l



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 12 sur 18

Aquatic Invertebrates

Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.

CE50 (Water flea, 2 DY): 180 mg/l

NOEC (Water flea, 2 DY): 100 mg/l

CE50 (Water flea, 21 DY): 100 mg/l

NOEC (Water flea, 21 DY): 56 mg/l

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

CE50 (Cladocère, 2 DY): > 100 mg/l

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich

CE50 (Water flea, 2 DY): 4,6 mg/l

NOEC (Water flea, 2 DY): 0,63 mg/l

Dibutyl phosphite

CE50 (Water flea (Daphnia magna), 48 h): 20,8 mg/l

C14-18 alpha-olefin epoxide, reaction products with boric acid

CE50 (Water flea, 2 DY): > 100 mg/l

NOEC (Water flea, 2 DY): 100 mg/l

CE50 (Water flea, 21 DY): 20 mg/l

NOEC (Water flea, 21 DY): 10 mg/l

Diphenylamine

CE50 (Water flea, 2 DY): 0,31 mg/l

Ethanol, 2,2'-iminobis-, N-tallow alkyl derivatives

CE50 (Water flea (Daphnia magna), 2 DY): < 1 mg/l

Toxicity for aquatic plants

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

CE50 (Green algae, 3 DY): 600 mg/l

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich

CE50 (Green algae, 3 DY): 63 mg/l

NOEC (Green algae, 3 DY): 0,313 mg/l

Dibutyl phosphite

CE50 (Seaweed (Pseudokirchneriella subcapitata), 72 h): 14,4 mg/l

C14-18 alpha-olefin epoxide, reaction products with boric acid

CE50 (Green algae (Selenastrum capricomutum), 3 DY): > 100 mg/l

Diphenylamine

CE50 (Green algae, 3 DY): 1,51 mg/l

Ethanol, 2,2'-iminobis-, N-tallow alkyl derivatives

CE50 (Seaweed, 3 DY): < 0,01 mg/l



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 13 sur 18

CE50 (Green algae(Selenastrum capricomutum), 3 DY): 0,029 mg/l
NOEC (Green algae(Selenastrum capricomutum), 3 DY): 0,01 mg/l

Toxicity for soil-dwelling living organisms

No data available

Toxicity for sediment-dwelling living organisms

No data available

Toxicity for terrestrial plants

No data available

Toxicity for terrestrial organisms

No data available

Toxicity for microorganisms

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
CE50 (Boue, 0,1 DY): > 1 000 mg/l

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich
CE50 (Boue, 0,1 DY): 10 000 mg/l
C14-18 alpha-olefin epoxide, reaction products with boric acid
CE50 (Mud, 0,1 DY): > 10 000 mg/l

12.1.2 Toxicity towards other organisms

As for the mixture: has not been a subject of a specific test

As for the components:

Petroleum base oil:

Very low toxicity. Toxicity for microorganisms: NOEL/10min > 1.93 mg/L (DIN 38412, DIN38409)

12.2 Persistence and degradability

12.2.1 Biodegradability

As for the mixture: has not been a subject of a specific test

As for components:

Petroleum base oil:

Not easily degradable (OECD301B).

12.2.2 Chemical degradation

As for the mixture: has not been a subject of a specific test



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 14 sur 18

As for components:

Petroleum base oil:

Not easily degradable

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
Formation of carbon dioxide 0 % (28 DY, OECD TG 301 B)

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich
Appauvrissement en oxygène 9,6 % (28 DY, OECD TG 301 C)

Alkyl borate

Formation de dioxyde de carbone 44,62 % (28 DY, OECD TG 301 B)

C14-18 alpha-olefin epoxide, reaction products with boric acid

Dissolved organic carbon (COD) 17,3 % (28 DY, Various)

Dissolved organic carbon (COD) 26,7 % (28 DY, Various)

Diphenylamine

Oxygen impoverishment 26 % (28 DY, OECD TG 301 D)

Ethanol, 2,2'-iminobis-, N-tallow alkyl derivatives

Oxygen impoverishment 60 % (28 DY, OECD TG 301 D)

12.3 Bioaccumulative potential

As for the mixture: has not been a subject of a specific test

As for the components:

Petroleum base oil:

It is possible that hydrocarbons (base-oil) accumulate (log Kow > 6).

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Bioconcentration factor (BCF): 1 584,89 (Measured)

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich

Bioconcentration factor (BCF): 27,54 (Measured)

Sharing coefficient n-octanol/water (log Kow)

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich

Log Kow: 4,1 (Measured)

C14-18 alpha-olefin epoxide, reaction products with boric acid

Log Kow: 6,33 (calculated)

Log Kow: 9,4 (calculated)



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 15 sur 18

Diphenylamine

Log Kow: 3,4 (calculated)

12.4 Mobility in soil

As for the mixture: has not been a subject of a specific test

As for the components:

Petroleum base oil:

The product is water-insoluble and mainly non-volatile. The product may penetrate soil until reaching groundwater surface. The degradation is going extremely slow in anaerobic conditions. Hydrocarbons (base oil) may be absorbed by soils organic material or sediments (log Kow > 6).

12.5 Results of PBT and vPvB assessment

As for the mixture: has not been a subject of a specific test

As for the components:

Petroleum base oil:

This substance is not considered as persistent, neither bioaccumulative nor toxic (PBT). This substance is not considered as very persistent or very bioaccumulative (vPvB).

12.6 Other adverse effects

As for the mixture: has not been a subject of a specific test

As for the components:

Petroleum base oil:

The information given is based on data taken up from products with similar substances.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

· Recommendation:

Must not be disposed together with household waste.

· Waste disposal:

Do not allow product to reach sewage system.



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 16 sur 18

Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations.

SECTION 14 - TRANSPORT INFORMATION

14.1. UN number

ADR, IMDG, IATA: Not regulated

14.2. UN proper shipping name

· **ADR**

Not regulated

· **IMDG**

Not regulated

· **IATA**

Not regulated

14.3. Transport hazard class(es)

· **ADR**

Not regulated

· **IMDG, IATA**

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Individual precautions: The driver should not take action in case of cargo fire.

Keep public away from danger area.

IMMEDIATELY CONTACT POLICE AND FIREMEN.

Other information: None.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code"

Not identified.



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 17 sur 18

SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Be ensured that all notation or local regulations are observed.

European regulatory guidelines:

- Regulation (CE) n° 1907/2006 of the European Parliament and of the Council of 18 December 2006 for Registration, Evaluation, Authorisation and Restriction of Chemical substances, as well as restrictions applicable to these substances (REACH), and establishing a European Chemicals Agency modifying directive 1999/45/CE and repealing Commission Regulation (CEE) n° 793/93 of Council Regulation (CE) n° 1488/94 of the Commission as well as directive 76/769/CEE of Council and directives 91/155/CEE, 93/67/CEE, 93/105/CE and 2000/21/CE of the Commission, with modifications.
- Regulation (CE) n° 1272/2008 of the European Parliament and of the Council of 16 December 2008 for classification, labelling and packaging of substances and mixtures, modifying and repealing directives 67/548/CEE and 1999/45/CE and modifying the regulation (CE) n° 1907/2006, with modifications.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16 - AUTRES INFORMATIONS

Symbols and hazard phrases used in this document section 3:

H290 – May be corrosive to metals

H301 – Toxic if swallowed

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H311 – Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 – Causes serious eye irritation

H331 – Toxic if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

H413 – May cause long lasting harmful effects to aquatic life

Since conditions or methods of use are not under our control, we assume no liability and expressly disclaim all liability for the use of this product. The information contained hereby is considered as true and accurate, but



SAFETY DATA SHEET

Conforme to réglementation 453/2010 - REACH

KENNOL CVT FLUID

Replace version xx/xx/xxxx

FDS :239-125750-170316

17/03/2016

Page 18 sur 18

all declarations or suggestions are made without warranty of any kind, either expressed or implied, as to the accuracy of the information, the hazards associated with this product or results that could be obtained with the use of such product. The respect of all governmental, provincial and local regulations is left to the sole responsibility of the user.