

FDS:1001-165310-170217

Conforme to reglementation 453/2010 - REACH

#### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

17/02/2017 Page 1 sur 15

### SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

- Product name: KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

- Commercial use: Windscreen Wash (for more details, please report back to the technical manual)

### 1.3. Details of the supplier of the Safety Data Sheet

Fournisseur ACCOR LUBRIFIANTS SA

Adresse : 8 Rue du Mans - BP 30406 - 49304 CHOLET CEDEX

Téléphone : 02.41.75.26.70

Télécopie : 02.41.62.67.02

Contact e-mail: emilie.auribault@accor-lubrifiants.com

## 1.4. Emergency telephone number

In France, the valid emergency number is the ORFILA (INRS) number: + 33 (0)1 45 42 59 59. This telephone number gives contacts of all French poison centers ("centres anti-poison et de toxicovigilance"). These information centers provide you with free medical advice (except the cost of call), 24 hours a day, 7 days a week. For the information related to other countries, see the web page dedicated to national helpdesks of the ECHA website (European Chemicals Agency) that lists all the information by country: <a href="http://echa.europa.eu/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks/">http://echa.europa.eu/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks/</a>

### SECTION 2 - HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

#### Classification CE 1272/2008 (CLP)

H226 – Flammable liquid – category 3 – Attention – (CLP : Flam. Liq. 3)

H319 – Eye irritation – category 2 – Attention - (CLP Eye Irrit. 2)

\_



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 2 sur 15

### 2.2. Label elements

### Label Conforms to Norm (CE) N° 1272/2008 (CLP):

# Hazard pictogram(s):





FDS:1001-165310-170217

Signal word(s): ATTENTION

### **Hazard statement(s):**

H226 Flammable liquid and vapour H319 Causes serious eye irritation

## Precautionary statement(s) - Prevention

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking

P233 - Keep container tightly closed

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P264 - Wash contaminated skin thoroughly after handling

## Precautionary statement(s) - Intervention

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 – If eye irritation persists: Get medical advice/attention.

## **Precautionary advice- Storage**

P403+P235 - Store in a well-ventilated place. Keep cool.

### **Precautionary advice - Elimination**

P501 - Dispose of contents/container to a hazardous waste collection center, as per national regulation

Additional phrase(s): Contains: Perfume

### 2.3. Other hazards

\* Irritating to the mucous membranes



FDS:1001-165310-170217

Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 3 sur 15

\* Ingestion has the following effects: nausea, vomiting, central nervous system depression, unconsciousness, similar symptoms to those presented by drunkenness.

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

## 3.2. Mixtures

- <u>Chemical nature</u>: formulated from demineralized water, alcohols and various additives.
- Dangerous components:

			NUMBERS
COMPONENTS	Percentage (in weight)	CLP Classification (EC) No 1272/2008	INDEX CE CAS Registration
ETHANOL	< 40 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319	603-002-00-5 200-578-6 64-17-5 01-2119457610-43
Ethane-1,2-diol	< 5%	Toxicité aigüe classe 4 H302 H373	603-027-00-1 203-473-3 107-21-1 01-2119456816-28
Sodium etasulfate	< 0.15 %	Skin Irrit. 2, H315 Eye Dam. 1, H318	204-812-8 126-92-1 01-2119971586-23

The whole of the text of risk phrases and hazard statements of this section 3 appears in Section 16.

## **SECTION 4 - FIRST AID MEASURES**

## 4.1. Description of first aid measures

If feeling unwell seriously or persistently, immediately seek medical attention

## Inhalation:

Move the subject away from the polluted area.



Conforme to reglementation 453/2010 - REACH

#### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 4 sur 15

FDS :1001-165310-170217 1
Take affected person into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

In the event of faintness, consult a doctor.

#### Skin contact:

Wash the skin with soap and water.

In case of persistent irritation of the skin, consult a doctor.

## Eye contact:

Rinse out with plenty of water for at least 10 minutes with the eyelid held wide open. Consult an ophthalmologist if the irritation persists.

#### Ingestion:

Do not induce vomiting. Never give anything to drink if the person is unconscious. Consult a physician or contact a poison control centre.

Move the person who is vomiting from his back onto his side.

#### 4.2. Most important symptoms and effects, both acute and delayed

Liquids or vapours may cause eye irritation.

This product may cause a slight skin irritation in case of repeated or prolonged contact.

Ingestion may have the following effects:

Central nervous system depression.

Nausea, vomiting.

Symptoms similar to that of being intoxicated by alcoholic drinks.

Inhalation of strong concentrations may cause temporary respiratory irritation, headaches, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

No other important information available.

## SECTION 5 - FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

<u>Suitable extinguishing media</u>: CO2, extinguishing powder or water pulverized. Fight large fires with water spray or alcohol resistant foam.

Adapt extinguishing measures to the environment.

Unsuitable extinguishing media for safety reason: full water jet.



Conforme to reglementation 453/2010 - REACH

#### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

FDS :1001-165310-170217 17/02/2017 Page 5 sur 15

### 5.2. Special hazards arising from the substance or mixture

Vapours with source of ignition, can create a sudden burst of flames.

## 5.3. Advice for firefighters

· Special safety equipment:

Wear a self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

· Other indications:

Use water to cool exposed containers.

Fire product residues and contaminated water must be disposed of according to administrative directives.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Wear safety equipment. Keep away non-protected persons.

### **6.2. Environmental precautions**

Do not allow product to reach sewage system or any water course. Inform respective authorities in case product reaches water or sewage system. Do not discharge into the drains/surface waters/groundwater.

## 6.3. Methods and material for containment and cleaning up

Pick up with suitable absorbent material (sand, binders, universal binders, sawdust). Make sure there is sufficient ventilation.

### **6.4. Reference to other sections**

To obtain information about safe handling, please see chapter 7.

To obtain information about personal protective equipment, please see chapter 8.

To obtain information about elimination, please see chapter 13.

### SECTION 7 - HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### **Manipulations**:

Do not eat, drink or smoke when using this product.

Store in a well-ventilated workplace.



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 6 sur 15

Breathing must be protected when large quantities are decanted without exhaust ventilation.

### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke

Protect against electrostatic charges.

FDS:1001-165310-170217

Appropriate equipment to face fire, spills and leaks must be easily reachable.

## 7.2. Conditions for safe storage, including any incompatibilities

· Requirements to be met by storerooms and containers

Store in a cool location.

Provide solvent-resistant and impermeable floor.

· Information about storage in one common storage facility

Not necessary.

### · Other information about storage facility:

Keep receptacle tightly sealed

Store in cool, dry conditions in well-sealed receptacles.

Keep away from heat and direct sunlight.

## 7.3. Specific end use(s)

No other important information available

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1. Control parameters

Components presenting critical values that have to be monitored at the workplace:

## 64-17-5 Ethyl alcohol

VME Instantaneous value: 9500 mg/m³, 5000 ppm

Long term value: 1900 mg/m<sup>3</sup>, 1000 ppm



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 7 sur 15

## ETHANE-1,2-DIOL

## Valeurs limites sur les lieux de travail

FDS:1001-165310-170217

N°	Dénomination de la substance	N° CAS		N° CE	
1	éthane-1,2-diol	107-21-1		203-473-3	
	2000/39/EWG				
	Ethylene glycol				
	VLE	104	mg/m³	40	ml/m³
	VME	52	mg/m³	20	ml/m³
	Résorbtion de l'épiderme / sensilibisateur	Skin			
	Valeurs limites d'exposition professionnelle aux agent chim	iques en Franc	е		
	Ethylèneglycol				
	vapeurs				·
	VLE	125	mg/m³	50	ml/m³

### Valeurs DNEL et PNEC

### valeurs DNEL (travailleurs)

N°	Dénomination de la substanc	e		N° CAS / CE	
	Voie d'exposition	durée d'action	effet	Valeur	
1	éthane-1,2-diol			107-21-1	
				203-473-3	
	dermale	(chronique) à long terme	systémique	106	mg/kg/jour
	par inhalation	(chronique) à long terme	local	35	mg/m³

## valeurs DNEL (consommateur)

N°	Dénomination de la substance		N° CAS / CE		
	Voie d'exposition	durée d'action	effet	Valeur	
1	éthane-1,2-diol			107-21-1	
				203-473-3	
	dermale	(chronique) à long terme	systémique	53	mg/kg/jour
	par inhalation	(chronique) à long terme	local	7	mg/m³

#### valeurs PNEC

N°	Dénomination de la substance		N° CAS / CE	
	compartiment écologique	Туре	Valeur	
1	éthane-1,2-diol		107-21-1	
			203-473-3	
	Eau	eau douce	10	mg/l
	Eau	eau marine	1	mg/l
	Eau	eau douce sédiment	20,9	mg/kg
	Eau	Eau dégagement intermittent	10	mg/l
	sol	-	1,53	mg/kg
	station d'épuration des eaux résiduaires (STP)	-	199,5	mg/l

## Additional comments:

The present document uses lists that were valid during its compilation.

### 8.2. Exposure controls

The appropriate control measures for a particular workplace depend on the way the product is used and on potential exposure.

## Personal protective equipment:



Conforme to reglementation 453/2010 - REACH

#### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 8 sur 15

· General protection and hygiene measures:

FDS:1001-165310-170217

Wash hands thoroughly before breaks and when finishing work.

### · Breathing protection:

Use suitable respiratory equipment if ventilation is insufficient.

In case of exposure risk above the regulated exposure limits values, it is advised to wear respiratory protective equipment adapted to risks.

### · Hands protection:

The glove material must be waterproof and resistant to the product/ the substance / the preparation. Choice of the glove material according to the penetration time, the infiltration and the degradation rate.

#### · Glove material

The choice of the appropriate material depends not only on the material, but also on other quality criteria that may vary from a manufacturer to the other. Since the product represents a preparation composed of several substances, the resistance of the glove material cannot be calculated in advance and must, thus, be controlled before its use.

· Penetration time of glove material

The precise penetration time is to be determined by the manufacturer of the protection gloves and is to be observed.

· Eyes protection: Protection goggles

· Body protection du corps: Protective clothing

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Appearance

Aspect: Liquid

Density at 20°C (g/cm3): 0,94

Colour: Pinkish orange
Smell: alcohol feature
pH value: 8 units pH typical
Flash point (closed beaker) (°C):
Freezing point (°C) : -30

Flammability (solid, gaseous): Not applicable.

Ignition temperature: Not defined

Self-inflammation: the product does not combust spontaneously.

Risk of explosion: the product is not explosive; however explosive air/vapour mixtures are possible.

Air explosure limits for pure ethanol:

Below: 3,3 Vol % Above: 19 Vol %

Vapour pressure at 20°C: Not defined



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 9 sur 15

Solubility: complete in water

FDS:1001-165310-170217

Partition coefficient (n-octanol/water): Not defined

### 9.2. Other information

No other important information available

## SECTION 10 - STABILITY AND REACTIVITY

## 10.1. Reactivity

No data available

### 10.2. Chemical stability

Stable when used and stored normally

### 10.3. Possibility of hazardous reactions

Dangerous reactions: none when used normally. Dangerous properties: none when used normally.

### 10.4. Conditions to avoid

High temperature

### 10.5. Incompatible materials

Powerful oxidisers, alkaline metals, aluminium.

## 10.6. Hazardous decomposition products

No hazardous decomposition products known

## SECTION 11 - TOXICOLOGICAL INFORMATION

## 11.1. Information on toxicological effects

Toxicological information referring to ingredients.

### **ETHANOL**

Acute toxicity (CAS: 64-17-5)

Acute toxicity (DL50 oral): > 2000 mg/kg Rat

Acute toxicity (DL50 dermal): > 2000 mg/kg Rabbit

Acute toxicity (CL50 by inhalation): > 20 mg/l (vapeurs) Mouse 4 hours



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 10 sur 15

## Skin corrosion/skin irritation:

Erythema and eschar formation

FDS:1001-165310-170217

Very light Erythema (barely noticeable) (1). Erythema well defined (2).

No irritation.

## Serious eye damage/eye irritation

Slightly irritating

#### **Respiratory sensitization**

Not available

### Skin sensitization

Guinea Pig Maximization Test (GPMT: Guinea Pig Maximisation Test): Guinea Pig

Non-sensitizing.

### Mutagenicity on germ cells:

Genotoxicity - In Vitro

Gene mutation:

Negative.

### Carcinogenicity:

Not available.

## Toxicity for the reproduction - Fertility

Not available.

## **Toxicity for the reproduction - Development**

Not available.

# <u>Specific toxicity for some target organs – repeated exposure:</u>

STOT – Repeated exposures

DSET 1730 mg/kg Oral

#### **Target organs**

Tractus gastro-intestinal Liver

Inhalation: Nausea, headache, drunken state

## Skin contact

No specific health warnings noted. Not considered a skin sensitizer.

### Eye contact

Irritating for eyes.

Ingestion: Drunken state that can lead to alcoholic coma.

Additional information: Long term exposure: may cause the same disorder as narcotic action.



FDS:1001-165310-170217

Conforme to reglementation 453/2010 - REACH

## **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 11 sur 15

# ETHANE-1,2-DIOL

Toxicité orale aiguë	
DL 50	7712 mg/kg
Espèces	rat
Source	CSR
Toxicité dermale aiguë	
DL 50	> 3500 mg/kg
Espèces	souris
Source	CSR
Source	COIT
Toxicité aiguë par inhalation	
CL 50	> 2,5 mg/l
Durée d'exposition	6 h
Espèces	rat
Source	CSR
Corrosion cutanée/irritation cutanée	
Espèces	lapin
Source	CSR
Évaluation	Non irritant
Lésions oculaires graves/irritation oculair	
Espèces	lapin
Source	CSR
Evaluation	Non irritant
Sensibilisation respiratoire ou cutanée	
Voie d'exposition	Peau
Espèces	cobaye
Source	CSR
Évaluation	non sensibilisant
Mutagénicité sur les cellules germinales	
Source	CSR
Remarque	Pas de données expérimentales disponibles sur la génotoxicité.
<u> </u>	T do de definices experimentales disperimes our la generaxione.
Toxicité pour la reproduction	
Source	CSR
Remarque	Pas de données expérimentales disponibles sur des effets toxiques sur la
	reproduction.
Cancérogénicité	
Source	CSR
Remarque	Pas de données expérimentales disponibles sur des effets cancérogènes.
<u> </u>	
Toxicité spécifique pour certains organes	cibles — exposition unique
Aucune donnée disponible	
Toxicité spécifique pour certains organes	cibles — exposition répétée
Aucune donnée disponible	
Danger par aspiration	
Aucune donnée disponible	
Augune defined disperiible	

# SECTION 12 - ECOLOGICAL INFORMATION

## 12.1. Toxicity

· Aquatic toxicity: No other important information available.



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 12 sur 15

Toxicological information referred to ingredients.

FDS:1001-165310-170217

## ETHANE-1,2-DIOL

Toxicité sur poissons		
CL50	72860	mg/l
Durée d'exposition	96	h
Espèces	Pimephales promelas	
Source	CSR	

Toxicité sur daphnies			
CE50	>	100	mg/l
Durée d'exposition		48	h
Espèces	Daphnia magna		
Source	CSR		

Toxicité sur algues	
CE50	6500 - 13000 mg/l
Durée d'exposition	96 h
Espèces	Pseudokirchneriella subcapitata
Source	CSR

Toxicité sur bactéries			
CE 20	>	1995	mg/l
Durée d'exposition		30	min
Espèces	boue activée		
Source	CSR		

## 12.2. Persistence and degradability

Toxicological information referred to ingredients.

## ETHANE-1,2-DIOL

Biodégradabilité	
Source	CSR
Évaluation	facilement biodégradable
Evaluation	Technolic blodogradebio

Reaction dans les épurateurs

En cas d'introduction de faibles concentrations dans des stations d'épuration biologiques adaptées, altération de l'activité de dégradation des boues activées non probable.

## 12.3. Bioaccumulative potential

Toxicological information referred to ingredients.

# ETHANE-1,2-DIOL

Facteur de bioconcentration (FBC)	
Remarque	Non potentiellement bioaccumulatif.
Ocetticient de neutene ne cetenel/eeu	
Coefficient de partage: n-octanol/eau	

## 12.4. Mobility in soil

No other important information available.

· Other ecological information:



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx

FDS :1001-165310-170217 17/02/2017 Page 13 sur 15

Water hazard class 1 (D) (Self-assessment): low-polluting

Do not leave the product, not diluted or in big quantity, reach ground water, water course or sewage system.

### 12.5. Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### 12.6. Other adverse effects

No other important information available

## SECTION 13 - DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

· Recommendation:

Must not be disposed together with household waste.

· Waste disposal:

Do not allow product to reach sewage system.

Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations.

## SECTION 14 - TRANSPORT INFORMATION

## **14.1. UN number**

ADR, IMDG, IATA: UN 1170

## 14.2. UN proper shipping name

· ADR

UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, III, (D/E)

IMDG

ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

·IATA

**ETHANOL SOLUTION** 

### 14.3. Transport hazard class(es)



Conforme to reglementation 453/2010 - REACH

### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 14 sur 15

#### · ADR

Class 3 (F1) Flammable liquids.

FDS:1001-165310-170217



### · IMDG, IATA

Class 3 Flammable liquids. Label 3



## 14.4. Packing group

ADR Packing group: III IMO Packing group: III IATA Packing group: III

## 14.5. Environmental hazards

IMDG- Marine pollution: NO

Spill and leak procedure: Clean up the leakage or the losses, even minor if possible without taking unnecessary

risks.

## 14.6. Special precautions for user

Individual precautions: The driver should not take action in case of cargo fire. Emergency measures in the event of an accident: No open flames. Do not smoke

Keep public away from danger area.

IMMEDIATELY CONTACT POLICE AND FIREMEN.

Other information: None.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code"

The mixture is not intended for bulk transport.

# SECTION 15 - REGULATORY INFORMATION



FDS:1001-165310-170217

Conforme to reglementation 453/2010 - REACH

#### **KENNOL LG-30 ANTI FROST CANDIED CHESTNUTS**

Replaces version xx/xx/xxxx 17/02/2017

Page 15 sur 15

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Be ensured that all notation or local regulations are observed. European regulatory guidelines:

- Regulation (CE) n° 648/2004 referring to detergents
- Regulation (CE) n° 1907/2006 of the European Parliament and of the Council of 18 December 2006 for Registration, Evaluation, Authorisation and Restriction of Chemical substances, as well as restrictions applicable to these substances (REACH), and establishing a European Chemicals Agency modifying directive 1999/45/CE and repealing Commission Regulation (CEE) n° 793/93 of Council Regulation (CE) n° 1488/94 of the Commission as well as directive 76/769/CEE of Council and directives 91/155/CEE, 93/67/CEE, 93/105/CE and 2000/21/CE of the Commission, with modifications.
- Regulation (CE) n° 1272/2008 of the European Parliament and of the Council of 16 December 2008 for classification, labelling and packaging of substances and mixtures, modifying and repealing directives 67/548/CEE and 1999/45/CE and modifying the regulation (CE) n° 1907/2006, with modifications.

### 15.2. Chemical Safety Assessment

Not applicable.

## SECTION 16 - OTHER INFORMATION

#### **Modifications indications**

1<sup>st</sup> version

## Symbols and hazard phrases used in this document section 3:

H225 - Highly flammable liquid and vapour

H302: Harmful if swallowed.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H319 - Causes serious eye irritation.

H373: May cause damage to organs through prolonged or repeated exposure

Since conditions or methods of use are not under our control, we assume no liability and expressly disclaim all liability for the use of this product. The information contained hereby is considered as true and accurate, but all declarations or suggestions are made without warranty of any kind, either expressed or implied, as to the accuracy of the information, the hazards associated with this product or results that could be obtained with the use of such product. The respect of all governmental, provincial and local regulations is left to the sole responsibility of the user.