

AUTOMATIC DEXRON III

PRODUCT DESCRIPTION

KENNOL AUTOMATIC DEXRON III is a fully synthetic oil developed for automatic and semi-automatic gearboxes and torque converters, for which a DEXRON III or MERCON type fluid is recommended. KENNOL AUTOMATIC DEXRON III is also recommended by manufacturers for the lubrication of manual gearboxes and power steering.

PROPERTIES

KENNOL AUTOMATIC DEXRON III is formulated from synthetic bases and top level performance additives to provide with special features, such as :

FEATURES	BENEFITS
Exceptional thermal and shearing stability	Optimal performance over time Extends the life of the system and improves its performances in severe usage conditions
Good air-release properties	No cavitation problems

SPECIFICATIONS

KENNOL AUTOMATIC DEXRON III has been developed to meet the highest international standards, including :

GM	Dexron III
Ford	Mercon
Allison	C4
Viscosity @ 40°C, cSt	37
Viscosity @ 100°C, cSt	7,8
Viscosity Index	185
Density @ 20°C	0,84
Pour Point, °C	<-40
Flash Point, °C	>190

KENNOL AUTOMATIC DEXRON III has been mainly developed to answer the needs of demanding applications, such as racing and performance vehicles, as well as every situation pushing the gearboxes and torque converters more than usual.

Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_AUTOMATIC_DEXRON_3_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2013 KENNOL. All rights reserved.