

# CHALLENGE

## 5W40 4T

### PRODUCT DESCRIPTION

KENNOL CHALLENGE 5W40 4T is a 100% synthetic lubricant for street and off-road motorcycles, equipped with 4-stroke engines, with or without integrated gearboxes and wet or dry clutches.

### PROPERTIES

KENNOL CHALLENGE 5W40 4T is formulated from synthetic bases and “new generation” additives providing outstanding level of performances :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
Extreme pressure additives	Good lubrication of integrated gearboxes
Low viscosity at low temperature	Easy gear shift and starting in cold weather
Low volatility	Guarantees low oil consumption
Exceptional thermal and shearing stability	Optimal protection over time and respect of drain intervals
High lubricating power	Enables high operational safety

### SPECIFICATIONS

KENNOL CHALLENGE 5W40 4T has been developed to meet the highest international standards, including :

SAE	5W40
JASO	MA2
API	SL
Viscosity @ 40°C (cSt)	83
Viscosity @ 100°C (cSt)	13,8
Viscosity Index	171
Viscosity CCS (cP)	5800 (at -30°C)
Density @ 20°C	0,852
Pour Point (°C)	< -35
Flash Point, °C	>210

KENNOL CHALLENGE 5W40 4T has been mainly developed to answer the needs of demanding applications, such as competition motorcycles, but remains highly recommended for multi-purposes applications. Because this product was born on the track.

Direct download here : [http://www.kennol.com/FT/KENNOL\\_CHALLENGE\\_5W40\\_4T\\_EN.pdf](http://www.kennol.com/FT/KENNOL_CHALLENGE_5W40_4T_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.