

GREASING ADHESIVE

PRODUCT DESCRIPTION

KENNOL GREASING ADHESIVE is a multipurpose grease for difficult lubricating especially resistant to rust, water or high temperature.

It is ideal for the lubrication of civil engineering equipment and machine-tool working under heavy load or at high temperature. Also suitable for the general lubrication of trucks (articulations, bearings, trailer turntables).

PROPERTIES

KENNOL GREASING ADHESIVE bears the following features:

FEATURES	BENEFITS
«Extreme pressure» additives	Reduced wear of components in movement.
Longer lubrication periods	
Insoluble in water, even boiling	

SPECIFICATIONS

KENNOL GREASING ADHESIVE has been developed to exceed the highest international standards, including:

	NLGI 2
Soap nature	Complex X
Colour	Green
Appearance	Smooth
Penetration [NF T 60-132] (1/10 mm)	265/295
Limit temperature of use (°C)	-20 to +150
Trial 4 balls welding load (kg)	315
Dropping point [METTLER] (°C)	190

Direct download here: http://www.kennol.com/FT/KENNOL_GREASING_ADHESIVE_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2014 KENNOL. All rights reserved.