

## IGNITION 0W40

### PRODUCT DESCRIPTION

KENNOL IGNITION 0W40 is a 100% synthetic lubricant specially designed to provide optimum protection for latest generation PETROL and DIESEL engines.

### PROPERTIES

KENNOL IGNITION 0W40 is formulated from selected synthetic bases and top level performance additives to provide with special features, such as :

FEATURES	BENEFITS
High fluidity at low temperature	For sure starting in extremely low temperatures.
Low volatility	Allows low oil consumption
Very high dispersing power	Cleans up deposits (sludge and varnish)
Very high thermal stability	Guarantees good protection at high temperature

### SPECIFICATIONS

KENNOL IGNITION 0W40 has been developed to meet the highest international standards, including :

<b>SAE</b>	<b>0W40</b>
<b>ACEA</b>	<b>A3/B4</b>
<b>API</b>	<b>SN/CF</b>
<b>VW</b>	<b>502.00/505.00</b>
<b>MB</b>	<b>229.5</b>
<b>BMW</b>	<b>LL-01</b>
<b>PORSCHE</b>	<b>A40</b>
Viscosity @ 40°C (cSt)	80
Viscosity @ 100°C (cSt)	14
Viscosity Index	186
Viscosity CCS (cP)	6000 (at -35°C)
Density @ 20°C	0,845
Viscosity HTHS (at 150 °C under high shear 10 <sup>6</sup> s-1) (cP)	> 3,5
Pour Point, °C	< -40
Flash Point, °C	>210
TBN (mg KOH/g)	9,5

KENNOL IGNITION 0W40 has been mainly developed to answer the needs of specific engines featuring direct injection. Because this product was born on the track.

Direct download here : [http://www.kennol.com/FT/KENNOL\\_IGNITION\\_0W40\\_EN.pdf](http://www.kennol.com/FT/KENNOL_IGNITION_0W40_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.  
© 2013 KENNOL. All rights reserved.