

MOTORACING 2T

PRODUCT DESCRIPTION

KENNOL MOTORACING 2T is a top level fully synthetic oil developed for 2-stroke engines motorcycles operating in racing environment or under extreme conditions (very high engine speed and heavy loads).

Kennol MOTORACING 2T is compatible with unleaded petrol.

PROPERTIES

KENNOL MOTORACING 2T is formulated from synthetic bases and "new generation" additives providing excellent properties :

FEATURES BENEFITS			
Antiwear and detergent properties	Prevents clogging up and wear of pistons		
Selected synthetic bases	Reduced fumes and clogging in the exhaust system		
High lubricating power	Optimal operational safety		

SPECIFICATIONS

KENNOL MOTORACING 2T has been developed to meet the highest international standards, including :

API	TC-TSC3	
JASO	FD	
ISO	L-EGD	
Viscosity @ 40°C (cSt)	62	
Viscosity @ 100°C (cSt)	10,2	
Viscosity Index	152	
Density @ 20℃	0,882	
Flash Point, °C	>110	

KENNOL MOTORACING 2T has been specifically developed to answer the needs of high-performance 2-stroke motorcycle. Because this product was born on the track.

 ${\tt Direct\ download\ here: http://www.kennol.com/FT/KENNOL_MOTORACING_2T_EN.pdf}$

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2013 KENNOL. All rights reserved.