

REVOLUTION 950-A 0W30

PRODUCT DESCRIPTION

KENNOL REVOLUTION 950-A 0W30 is a high tech fully synthetic engine lubricant especially formulated to lubricate last generation diesel FORD engines (TDCI Duratorq 1.5L, 1.6L, and 2.0L)

This lubricant has to be used when the specification FORD M2C 950-A is required

PROPERTIES

KENNOL REVOLUTION 950-A 0W30 is formulated from synthetic bases and high technology additives enabling the improvement of the following features:

FEATURES	BENEFITS
Mid-SAPS	Protection of post-treatment systems
High resistant oil film	Optimal protection even in severe use conditions
Low HTHS Viscosity	Fuel consumption reduced

SPECIFICATIONS

KENNOL REVOLUTION 950-A 0W30 has been developed to meet the following international standards:

SAE	0W30
ACEA	C2
FORD	WSS-M2C-950-A
Viscosity @ 40°C (cSt)	43,7
Viscosity @ 100°C (cSt)	9,3
Viscosity index	163
CCS viscosity (cP) -35°C	5077
Density @ 20°C	0,841
HTHS viscosity (@ 150 °C shearing 10 ⁶ s ⁻¹) (cP)	3,0
Sulfated ash (%)	0,80
TBN (mg KOH/g)	8,3

KENNOL REVOLUTION 950-A 0W30 has been formulated to develop the whole potential of modern engines. Because this product is born on the track.

Direct download here: http://www.kennol.com/FT/KENNOL_REVOLUTION_950-A_0W30_EN.pdf

For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2018 KENNOL. All rights reserved.