

**SAE 50
CF/SF****PRODUCT DESCRIPTION**

KENNOL SAE 50 is a monograde oil for diesel engines, including turbo-charged, of trucks, civil engineering equipment and passenger cars.

Its high viscosity allows to limit the oil consumption.

It can also be used for petrol engines.

It is miscible with all standard engine oils.

PROPERTIES

KENNOL SAE 50 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear, detergent, dispersant, antirust and antioxidation additives.	Preservation of the engine cleanliness over time.
High viscosity at high temperature.	Oil consumption reduction.
SAE 50 grade.	Particularly suitable for hot climate countries.

SPECIFICATIONS

KENNOL SAE 50 has been developed to meet the highest international standards, including :

SAE	50
API	CF/SF
MB	227.0
MIL.L.	2104 D
Viscosity @ 40°C (cSt)	210
Viscosity @ 100°C (cSt)	19,1
Viscosity Index	100
Density @ 20°C	0,897
Viscosity HTHS (at 150 °C under high shear 10 ⁶ s-1) (cP)	> 3.5
Pour Point (°C)	< -20
Flash Point, °C	> 210
TBN (mg KOH/g)	11

KENNOL SAE 50 has been mainly developed to answer the needs of drivers asking for an alternative solution with their petrol or diesel engine. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_SAE_50_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly. © 2014 KENNOL. All rights reserved.