

SCOOTER 2T

PRODUCT DESCRIPTION

KENNOL SCOOTER 2T is a synthetic based oil developed for 2-stroke engines motorcycles and scooters operating in high rotation systems. KENNOL SCOOTER 2T can be used with separate or mixed lubricant system. For the dose refer to the manufacturers' recommendation.

KENNOL SCOOTER 2T is compatible with unleaded petrol.

PROPERTIES

KENNOL SCOOTER 2T is formulated from quality bases combined with high performance additives to provide with special features, such as :

FEATURES	BENEFITS
Selected synthetic bases	Reduced fumes and clogging in the exhaust system
Detergent and antiwear properties	Prevent clogging up and wear of pistons

SPECIFICATIONS

KENNOL SCOOTER 2T has been developed to meet the highest international standards, including :

API	TC-TSC3
JASO	FD
ISO	L-EGD
Viscosity @ 40°C (cSt)	70
Viscosity @ 100°C (cSt)	10,2
Viscosity Index	130
Density @ 20°C	0,866
Flash Point, °C	>110

KENNOL SCOOTER 2T has been specifically created for scooters operating in high performance situation and extreme conditions. Because this product was born on the track.

Direct download here: http://www.kennol.com/FT/KENNOL_SCOOTER_2T_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2013 KENNOL. All rights reserved.