

# SUPERPLUS 15W40

## PRODUCT DESCRIPTION

KENNOL SUPERPLUS 15W40 is a high quality mineral lubricant for mixed fleet, intended for petrol or diesel engines, turbocharged or not, driving long road-route, mixed route or door-to-door, all year round.

## PROPERTIES

KENNOL SUPERPLUS 15W40 is formulated from bases and new generation additives to provide the following features:

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
High viscosity at high temperature	Very good protection at high temperature
Low volatility	Oil consumption reduction
High lubricating power	Improves safety at high power

## SPECIFICATIONS

KENNOL SUPERPLUS 15W40 has been developed to meet the following international standards:

SAE	15W40
API	SG/CE
MIL.L.	2104 E / 46152 E
MB	226.5 / 227.1 / 227.5
VW	505.00
CCMC	G4/D4/PD2
Viscosity @ 40°C (cSt)	102
Viscosity @ 100°C (cSt)	14.2
Viscosity index	140
Viscosity CCS (cP)	5800 (at -20°C)
Density @ 20°C	0.875
HTHS viscosity (@ 150 °C under high shear 10 <sup>6</sup> s-1) (cP)	> 3.5
Flow point, (°C)	< -25
Flash point, (°C)	> 210
TBN (mg KOH/g)	8.9

KENNOL SUPERPLUS 15W40 has been developed to bring a solution to drivers concerned by the performance and the endurance of their vehicle. Because this product was born on the track.

Direct download here : [http://www.kennol.com/EN/FT/KENNOL\\_SUPERPLUS\\_15W40\\_EN.pdf](http://www.kennol.com/EN/FT/KENNOL_SUPERPLUS_15W40_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.