

TOURING 10W30

PRODUCT DESCRIPTION

KENNOL TOURING 10W30 is a multi-grade high performance oil designed for recent gasoline engines (turbocharged, injection, with or without overhead camshaft) of passenger cars and light vans in various or severe service conditions (city or highway driving, high rotation speeds, "stop/start" system)

PROPERTIES

KENNOL TOURING 10W30 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
Low viscosity at low temperatures	Reduces wear at cold start
High dispersing power	Allows complete safety in urban drive

SPECIFICATIONS

KENNOL TOURING 10W30 has been developed to meet the highest international standards, including :

SAE	10W30
API	SL/CF
Viscosity @ 40°C (cSt)	72
Viscosity @ 100°C (cSt)	11
Viscosity Index	140
Viscosity CCS (cP)	6500 (@ -25°C)
Density @ 20°C	0,88
Viscosity HTHS (at 150 °C under high shear 10 ⁶ s-1) (cP)	> 3.5
Pour Point (°C)	< -30
Flash Point (°C)	> 180
TBN (mg KOH/g)	8,1

KENNOL TOURING 10W30 has been mainly developed to answer the needs of drivers asking for an alternative solution with their petrol or diesel engine. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_TOURING_10W30_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2015 KENNOL. All rights reserved.