

ASKING FOR ASPHALT

TOURING C3 5W40

PRODUCT DESCRIPTION

KENNOL TOURING C3 5W40 is a high-end 100% synthetic new generation lubricant for most makers, including Mid SAPS technology. Recommended for recent petrol and diesel turbo engines, equipped with intercooler, direct injection, common rail, or post-treatment device (three-way catalytic converter, particulate filter...).

PROPERTIES

KENNOL TOURING C3 5W40 is formulated from inovative synthetic bases combined with latest performance additives to provide with special features, such as :

FEATURES	BENEFITS
Mid-SAPS Technology	Allows important fuel saving and helps to protect environment
Very high detergent and dispersant properties	Ensures excellent engine protection and cleanness and reduces exhaust fumes
Very high thermal stability	Guarantees good protection at high temperature
Low volatility	Enables very low oil consumption

SPECIFICATIONS

KENNOL TOURING C3 5W40 has been developed to meet the highest international standards, including :

SAE	5W40
ACEA	C3
API	SN/CF
MB	229.31 / 229.51
BMW	LL-04
VW	502.00/505.00/505.01
PORSCHE	A40
OPEL	DEXOS2
RENAULT	RN 0700/0710

Viscosity @ 40°C (cSt)	85
Viscosity @ 100°C (cSt)	14
Viscosity Index	180
Viscosity CCS (cP)	6200 (@ -30°C)
Density @ 20°C	0,85
Viscosity HTHS (at 150 °C under high shear 10 ⁶ s-1) (cP)	3,8
Pour Point, °C	-37
Flash Point, °C	> 210
Volatility Noack 1H @ 250°C	11,5
TBN (mg KOH/g)	7,4

KENNOL TOURING C3 5W40 ahas been developed to unleash the potential of most modern engines, through a rational use of energy. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/KENNOL_TOURING_C3_5W40_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2016 KENNOL. All rights reserved.