



ASKING
FOR
ASPHALT

TRANSMISSION T04

SAE10

PRODUCT DESCRIPTION

KENNOL TRANSMISSION T04 SAE10 is a mineral high quality lubricant designed for the transmissions of civil engineering equipment.

KENNOL TRANSMISSION T04 SAE10 ensures the lubrication of transmissions, wet brakes, final drives.

PROPERTIES

KENNOL TRANSMISSION T04 SAE10 is formulated from bases and additives to provide with features, such as:

FEATURES	BENEFITS
Friction and antiwear properties	Components damage prevented, equipment life extended.
Good compatibility with elastomer and resins	Breakdown, failures and excessive noise reduced.
High stability in the time	Perfect working guaranteed, clutch slip under heavy load prevented.

SPECIFICATIONS

KENNOL TRANSMISSION T04 SAE10 has been developed to exceed the highest international standards, including:

SAE	10
API	CF
CATERPILLAR	T04
ALLISON	C4
KOMATSU MICRO CLUTCH	
ZF	TE-ML 03E
Eaton Fuller	
Viscosity @ 40°C (cSt)	35
Viscosity @ 100°C (cSt)	5,5
Viscosity index	98
Density at -20°C	0,885

Direct download here: http://www.kennol.com/FT/KENNOL_TRANSMISSION_T04_SAE10_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2014 KENNOL. All rights reserved.