

TRUCKING MT 5 10W40

PRODUCT DESCRIPTION

KENNOL TRUCKING MT 5 10W40 is a semi-synthetic 4 stroke very high performance oil for highly loaded 4 stroke engines and especially recommended for the lubrication of heavy truck, agricultural equipment and civil engineering EURO 1 to 5 engines, without particulate filters.

PROPERTIES

KENNOL TRUCKING MT 5 10W40 is formulated from bases combined with additives to provide with features, such as :

FEATURES	BENEFITS
«New generation» additives	Extended drain intervals (90000 to 120000 kms).
Low viscosity at low temperature	Fuel economy.

SPECIFICATIONS

KENNOL TRUCKING MT 5 10W40 has been developed to meet the highest international standards, including:

SAE	10W40
API	CI4
ACEA	E4 / E7
MAN	3277
SCANIA	LDF-2
VOLVO	VDS 3
MTU	DDC TYPE 3
RENAULT TRUCK	RXD/RLD-2
MERCEDES	MB 228.5
CUMMINS	CES 20077/78
DEUTZ	DQC III-10
MACK	EO-N/E0-M PLUS
Viscosity @ 40°C (cSt)	90,3
Viscosity @ 100°C (cSt)	13,6
Viscosity index	152
Density	0,882
Dynamic viscosity @ -25°C (cP)	6500

Direct download here: http://www.kennol.com/FT/KENNOL_TRUCKING_MT5_10W40_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2017 KENNOL. All rights reserved.