



ASKING
FOR
ASPHALT

MV3 20W50 SHPD

PRODUCT DESCRIPTION

KENNOL TRUCKING MV3 20W50 SHPD is a very high 4 stroke mineral performance oil developed for transport vehicles equipped with diesel engines turbo-charged or not, used in severe conditions, meeting EURO I, II, III or IV and used for long motorway driving, mixed routes or deliveries in urban area or operating on site.

PROPERTIES

KENNOL TRUCKING MV3 20W50 SHPD is formulated from bases combined with additives to provide with features, such as :

FEATURES	BENEFITS
Detergent, dispersing, antioxidant properties and high thermal stability	Extended drain intervals (45000 kms).
Grade 20W50	Grade particularly well adapted to hot country weather conditions
High Total Base Number	Action against sulfur contained in the fuel.

SPECIFICATIONS

KENNOL TRUCKING MV3 20W50 SHPD has been developed to meet the following international standards, including :

SAE	20W50
API	CI4 / SL
ACEA	E7-12 / B4-12
MAN	3275-1
VOLVO	VDS 3
RENAULT TRUCKS	RLD 2
CATERPILLAR	ECF-1a / ECF-2
MERCEDES	MB 228.3
CUMMINS	CES 20076 / 77 / 78
MACK	E0-M PLUS
Viscosity @ 40°C (cSt)	164
Viscosity @ 100°C (cSt)	18,5
Viscosity index	125
Density @ 20°C	0,888
Dynamic viscosity @ -15°C (cP)	9000

Direct download here: http://www.kennol.com/FT/KENNOL_TRUCKING_MV3_20W50_SHPD_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly. © 2015 KENNOL. All rights reserved.