

FASTRACK 10W30 4T

PRODUCT DESCRIPTION

KENNOL FASTRACK 10W30 4T is a semi synthetic lubricant for street and off-road motorcycles, equipped with 4-stroke engines, with or without integrated gearboxes and wet or dry clutches.

KENNOL FASTRACK 10W30 4T has been developed for motorcycles and recent scooters which need a grade 10W30.

PROPERTIES

KENNOL FASTRACK 10W30 4T is formulated from high quality bases and “new generation” additives providing outstanding level of performances :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
Extreme pressure additives	Good lubrication of integrated gearboxes
Very good thermal and shearing stability	High protection over time and respect of drain intervals
Low volatility	Guarantees low oil consumption
High lubricating power	Enables high operational safety

SPECIFICATIONS

KENNOL FASTRACK 10W30 4T has been developed to meet the highest international standards, including :

SAE	10W30
JASO	MA / MA2
API	SL
Viscosity @ 40°C (cSt)	70
Viscosity @ 100°C (cSt)	10,9
Viscosity Index	130
Viscosity CCS (cP)	6500 (at -25°C)
Density @ 20°C	0,866
Pour Point (°C)	< -30
Flash Point, °C	>210

KENNOL FASTRACK 10W30 4T has been mainly developed to answer the needs of demanding applications, such as competition motorcycles, but remains highly recommended for multi-purposes applications. Because this product was born on the track.

Direct download here : http://www.kennol.com/EN/FT/KENNOL_FASTRACK_10W30_4T_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2019 KENNOL. All rights reserved.