

GREASING EPOO

PRODUCT DESCRIPTION

KENNOL GREASING EP 00 is a high quality lithium grease for multiple uses recommended for the lubrication of reduction and motoreduction axles and for all centralized lubricating systems (e.g. Meca Fluid). It is also used as a sealant instead of some oils. It must be used when smooth grease EP 00 is recommended.

PROPERTIES

KENNOL GREASING EP 00 bears the following features:

FEATURES	BENEFITS
«Extreme pressure» additives	Reduced wear of components in movement.
Inhibitors of corrosion and oxidation	
Insoluble in water	

SPECIFICATIONS

KENNOL GREASING EP 00 has been developed to exceed the highest international standards, including:

	NLGI 00
Soap nature	Lithium
Colour	Amber
Appearance	Smooth
Penetration [NF T 60-132] (1/10 mm)	400/430
Corrosion Cu 3 h/100°C [ASTM D 4048]	1 b
Limit temperature of use (°C)	-35 to +135
EMCOR Test distilled water [NF T 60-135]	0
4 weld balls [ASTM D 2596] (kg)	250
4 wear balls 1 h/40 kg [ASTM D 2266] (mm)	0,5
Oxidation after 100 h [ASTM D 942] (psi)	Inf. to 6
Drop point [METTLER] (°C)	180

Direct download here: http://www.kennol.com/FT/KENNOL_GREASING_EPOO_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2014 KENNOL. All rights reserved.