

# HYDRA HM46

## PRODUCT DESCRIPTION

KENNOL HYDRA HM 46 is a hydraulic oil with antioxidant, anti-wear and anti-foam additives.

KENNOL HYDRA HM 46 is intended for all hydraulic circuits.

## PROPERTIES

KENNOL HYDRA HM 46 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Good demulsibility and antifoaming quality	Good energy transmission.
Antiwear, anticorrosion, antioxidant and extreme pressure additives	Protection of the circuit elements.
Neutral towards elastomers used in industry	
Compatible with silver-plated or bronze elements	

## SPECIFICATIONS

KENNOL HYDRA HM 46 has been designed to meet the highest international standards, including :

<b>ISO 3498</b>	<b>VG 46</b>
<b>DIN 51524-3</b>	<b>HLP</b>
<b>AFNOR NFE 48603</b>	<b>HM</b>
Viscosity @ 40°C (cSt)	46
Viscosity @ 100°C (cSt)	7
Viscosity Index	100
Density @ 20°C	0,87
Pour Point, °C	-25
Colour	Amber

KENNOL HYDRA HM 46 has been developed to answer the needs of demanding applications.