

HYDRA HM68

PRODUCT DESCRIPTION

KENNOL HYDRA HM 68 is a hydraulic oil with antioxidant, anti-wear and anti-foam additives.

KENNOL HYDRA HM 68 is intended for all hydraulic circuits and can also be used for ALFA-LAVAL Oil Type ALB vacuum pumps.

PROPERTIES

KENNOL HYDRA HM 68 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Good demulsibility and antifoaming quality	Good energy transmission.
Antiwear, anticorrosion, antioxidant and extreme pressure additives	Protection of the circuit elements.
Neutral towards elastomers used in industry	
Compatible with silver-plated or bronze elements	

SPECIFICATIONS

KENNOL HYDRA HM 68 has been designed to meet the highest international standards, including :

ISO 3498	VG 68
DIN 51524-3	HLP
AFNOR NFE 48603	HM
Viscosity @ 40°C (cSt)	68
Viscosity @ 100°C (cSt)	8,6
Viscosity Index	100
Density @ 20°C	0,882
Pour Point, °C	-20
Colour	Amber

KENNOL HYDRA HM 68 has been developed to answer the needs of demanding applications.

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2020 KENNOL. All rights reserved.