

HYDRA HV68

PRODUCT DESCRIPTION

KENNOL HYDRA HV 68 is a high quality hydraulic oil for use in all hydraulic systems on industrial machinery or on mobile plant (building site equipment, agricultural machinery, transport equipment).

It is especially recommended for hydraulic systems working outside at very different temperatures and meets the requirements of high pressure hydraulic systems.

PROPERTIES

KENNOL HYDRA HV 68 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
High viscosity index, good demulsibility and antifoaming quality	Good energy transmission.
Antiwear, anticorrosion, antioxidant and extreme pressure additives	Protection of the circuit elements.
Neutral towards elastomers used in industry	
Compatible with silver-plated or bronze elements	

SPECIFICATIONS

KENNOL HYDRA HV 68 has been designed to meet the highest international standards, including :

ISO 3498	VG 68
DIN 51524-3	HVLP
AFNOR NFE 48603	HV
DENISON	HF0
Color	Amber
Viscosity @ 40°C (cSt)	68
Viscosity @ 100°C (cSt)	10,9
Viscosity Index	147
Density @ 20°C	0,88
Flow Point, °C	-37
Flash Point, °C	220

KENNOL HYDRA HV 68 has been developed to answer the needs of demanding applications.

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2019 KENNOL. All rights reserved.