

TOURING 15W40

PRODUCT DESCRIPTION

KENNOL TOURING 15W40 is a high quality mineral motor oil, adapted for petrol or diesel passenger cars, equipped or not with turbo. Its wide viscosity range and its high viscosity index allow a use all year round, in urban area as well as for long motorway driving. This motor oil can also be used in trucks.

PROPERTIES

KENNOL TOURING 15W40 is formulated from high quality bases combined with modern performance additives to provide with special features, such as :

FEATURES	BENEFITS
Antiwear and detergent properties	Extends engine life
High viscosity	Very good protection at high temperatures
Low volatility	Guarantees low oil consumption
High lubricating power	Enables high operational safety

SPECIFICATIONS

KENNOL TOURING 15W40 has been developed to meet the highest international standards, including :

SAE	15W40
ACEA	A3/ B4/ E7
API	SL/ CF/ CI-4
MB	228.3
MAN	3275
VOLVO	VDS-2/ VDS-3
RENAULT	RLD-2
MACK	EO-M+/ EO-N
CUMMINS	CES 20077/ 20078
CAT	ECF-1A/ECF-2
DEUTZ	DQC-II/ DQC-III-10
DETROIT DIESEL	DDC 93K215
GLOBAL	DHD-1
JASO	DH-1
MTU	2.0
Viscosity @ 40°C (cSt)	109
Viscosity @ 100°C (cSt)	14.6
Viscosity Index	137
Viscosity CCS (cP)	6500 (à -20°C)
Density @ 20°C	0.88
Viscosity HTHS (at 150 °C under high shear 10 ⁶ s-1) (cP)	> 3.5
Pour Point (°C)	< -25
Flash Point, °C	> 210
TBN (mg KOH/g)	10.4

KENNOL TOURING 15W40 has been mainly developed to answer the needs of drivers asking for an alternative solution with their petrol or diesel engine. Because this product was born on the track.