



ASKING  
FOR  
ASPHALT

# TRUCKTRANS 85W140

## PRODUCT DESCRIPTION

KENNOL TRUCKTRANS 85W140 is an extreme pressure oil for transmissions, hypoid axles and reductions of vehicles and civil engineering equipment operating under severe conditions.

## PROPERTIES

KENNOL TRUCKTRANS 85W140 is formulated from bases and additives to provide with features, such as:

FEATURES	BENEFITS
Good viscosity index	Efficient lubrication of the bearings in cold weather. Wear protection at high temperature.
Antifoaming properties	Oil consumption and cavitation problems in pumps reduced.
Extreme pressure additives	Formation of a resistant «lubricating film».
Excellent oxidation stability	Extended drains intervals.

## SPECIFICATIONS

KENNOL TRUCKTRANS 85W140 has been developed to exceed the highest international standards, including:

<b>SAE</b>	<b>85W140</b>
<b>API</b>	<b>GL5</b>
<b>MIL.L.</b>	<b>2105D</b>
<b>VOLVO</b>	<b>97310</b>
Viscosity at 40°C (cSt)	430
Viscosity at 100°C (cSt)	29
Viscosity index	97
Density at 20°C	0,915
Colour	Amber
Flash Point (closed beaker) (°C)	> 170

Direct download here: [http://www.kennol.com/EN/FT/KENNOL\\_TRUCKTRANS\\_85W140\\_EN.pdf](http://www.kennol.com/EN/FT/KENNOL_TRUCKTRANS_85W140_EN.pdf)

All products may not be available locally. For more information, contact your distributor or visit [www.kennol.com](http://www.kennol.com). Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2020 KENNOL. All rights reserved.