



ULTIMA BRAKE DOT.4

PRODUCT DESCRIPTION

KENNOL ULTIMA BRAKE DOT 4 is a fully synthetic high performance brake fluid, especially developed for vehicles whom manufacturer requires a synthetic fluid.

Its very high dry and wet boiling points allow it to maintain a good braking efficiency when the brakes are extremely stressed and in wet weather.

BE CAREFUL :

- Do not use where a mineral fluid (LHM) is required
- Do not blend with silicon based fluids
- Avoid contact with paintworks
- Keep in a dry place

PROPERTIES

KENNOL ULTIMA BRAKE DOT 4 is formulated from high quality bases and additives to provide with special features, such as :

FEATURES	BENEFITS
High wet boiling point	Keep braking qualities in wet weather

SPECIFICATIONS

KENNOL ULTIMA BRAKE DOT 4 has been developed to exceed the highest international standards, including :

SAE	J1703F / J1704
FMVSS	116
DOT	4, 3
Viscosity @ -40°C (mm ² /s)	< 1500
pH	7,2
Water (%)	< 0,2
Dry Boiling Point (°C)	> 320
Wet Boiling Point (°C)	> 200

KENNOL ULTIMA BRAKE DOT 4 has been developed to answer the needs of control in extreme situations as well as every situation requiring more brake efficiency than usual. Because this product was born on the track.

Direct download here : http://www.kennol.com/FT/ULTIMA_BRAKE_DOT_4_EN.pdf

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2018 KENNOL. All rights reserved.